Technical Sheet

BASN17G

Ramme-søm 17° Plaststrimmel - Rund hoved, Takket skaft - HDG

The framing nail is used for wood to wood constructions. The round head gives a good visual end result and the plastic collation is not sensitive for wetness. The barbed shank increases withdrawal resistance.









Features

Features:

- Rundt hoved
- Takket skaft øger modstandsdygtigheden mod udtrækning
- Plaststrimmel 17°

Applications

Application:

- Framing wood to wood

BASN17G


Ramme-søm 17° Plaststrimmel - Rund hoved, Takket skaft - HDG

Teknisk data



Product Dimensions

Reference	Dimensioner										
	Best. nr.	Andre			Dimensioner[mm]						
		DB nr.	NOBB nr.	Antal pr. kasse	d[mm]	L[mm]	d_h[mm]	A_h[mm]	h_t[mm]	l_p[mm]	tf_{ix}[mm]
BASN17G2.8X50	75621	2055975	55841425	500	2.8	49.5	6.6	34.2	1	3.9	32.7
BASN17G2.8X55	75622	2055976	55841433	500	2.8	54.5	6.6	34.2	1	3.9	37.7
BASN17G2.8X65	75623	2055977	55841444	500	2.8	63.5	6.6	34.2	1	3.9	46.7
BASN17G2.8X75	75624 - 75619	2055978 - 2055973	55841452 - 55841917	500 / 1000	2.8	73.5	6.6	34.2	1	3.9	56.7
BASN17G3.1X90	75625 - 75620	2055979 - 2055974	55842844 - 55841414	500 / 1000	3	88	6.6	34.2	1	4.3	70



Product characteristic parameters

Reference	Nail characteristic parameters			
	Produktets karakteristiske egenskaber			
	Bøjningsstyrke - $My,_k$[Nm]	Karakteristisk udtræknings parameter - $f_{ax,k,90°}$[N/mm²]	Karakteristisk gennemtræks parameter - $f_{head,k}$[N/mm²]	Karakteristisk trækstyrke - $f_{tens,k}$[kN]
BASN17G2.8X50	2.6	4.9	22.6	4
BASN17G2.8X55	2.6	4.9	22.6	4
BASN17G2.8X65	2.6	4.9	22.6	4
BASN17G2.8X75	2.6	4.9	22.6	4
BASN17G3.1X90	3.9	5.4	20.9	4.8

Simpson Strong-Tie
A/S
Egeskovvej 33 8700
Horsens
tel: +45 8781 7400
info@strongtie.dk
Copyright by Simpson Strong-Tie®
Oplysningerne i dette dokument ejes eksklusivt af Simpson Strong-Tie® A/S.
De er kun gældende i forbindelse med produkter, som forhandles af Simpson Strong-Tie®