Technical Sheet

NCNG
Skåret søm - Varmgalvaniseret

This cut nail has various shapes and withstands rain. Used for nailing sills, frames and battens, etc., into wood.





Features

Features:

- Varmgalvaniseret
- Kileformet profil

Applications

Application:

- Wood to wood

Teknisk data

Product dimensions

Reference	Dimensioner														
	Best. nr.	Andre				Dimensioner[mm]									
		DB nr.	NOBB nr.	Antal pr. kasse	Vægt[kg]	d[mm]	L[mm]	d_h[mm]	d1[mm]	A_h[mm]	h_t[mm]	lg[mm]	l_p[mm]	tf_{ix}[mm]	Bit[mm]
NCNG4.0x75	75664	2056018	55837456	300	0.009	4	75	7.5	-	44.16	2.6	-	-	-	-
NCNG5.0x100	75665	2056019	55837460	165	0.016	5	100	8.5	-	56.72	2.6	-	-	-	-
NCNG5.0x150	75667	2056021	55837475	60	0.042	8	150	9	-	63.6	3.5	-	-	-	-
NCNG6.0x125	75666	2056020	55837486	100	0.025	6	125	9	-	63.6	3.5	-	-	-	-

Simpson Strong-Tie A/S
Egeskovvej 33 8700 Horsens
tel: +45 8781 7400
info@strongtie.dk

Copyright by Simpson Strong-Tie®
Oplysningerne i dette dokument ejes eksklusivt af Simpson Strong-Tie® A/S.
De er kun gældende i forbindelse med produkter, som forhandles af Simpson Strong-Tie® A/S.