
Technical Sheet

LTSFR

Skirting skrue rustfri hærdet

Used outdoor when laying solid wood flooring. The small screw head means that countersinking in the base material is improved, and the screw's design helps preventing wooden floors creaking. Corrosion resistance of the steel is compairable with traditional.





Features

Advantages

- 6 lobe drive
- Trim pan head
- Type 17 point
- Coarse thread with reverse thread

Applications

Support

- Fodpaneler til træ
- Sokkel til stål
- Massivt trægulv til træ

LTSFR
Skirting skrue rustfri hærdet

Teknisk data

Product dimensions

Reference	Dimensioner													
	Best. nr.	Andre				Dimensioner[mm]								
		DB nr.	NOBB nr.	Antal pr. kasse	Vægt[kg]	D[mm]	L[mm]	d_h[mm]	d_1[mm]	Ah[mm]	h_t[mm]	lg[mm]	lp[mm]	l-lg[mm]	Bit[mm]
LTSFR3.9X35	75514	2055869	55841743	250	0.002	3.9	35	5	2.2	-	-	23	-	12	TX10
LTSFR3.9X42	75515	2055870	55841758	250	0.002	3.9	42	5	2.2	-	-	27	-	15	TX10
LTSFR3.9X57	75516	2055871	55841762	250	0.002	3.9	57	5	2.2	-	-	37	-	20	TX10
LTSFR4.5X70	75517	2055872	55841777	250	0.004	4.5	70	5	2.8	-	-	46	-	24	TX15
LTSFR4.5X80	75518	2055873	55841781	250	0.005	4.5	80	5	2.8	-	-	50	-	30	TX15

Copyright by Simpson Strong-Tie®
Oplysningerne i dette dokument ejes eksklusivt af Simpson Strong-Tie® A/S.
De er kun gældende i forbindelse med produkter, som forhandles af Simpson Strong-Tie® A/S.