
Technical Sheet

VBS
VindueskarmC1:C2102skrue rustfri A4

Painted head to match colored steel plate work for windows. Primarely used for installation of window sills. The window sill screw can deal with aggressive environments. The underside of the head is tapered to ensure a good seal with the sheet or plate. The cutpoint prevents splitting of the frame wood.





Features

Features:

- Firkantet drev
- Lakeret panhead
- Rustfrit A4

Colors:

- 75520 = Umalet
- 75521 = Hvidmalet hoved
- 75522 = Sortmalet hoved

Applications

Application:

- Vindueskarm til træ
- Metalplade til træ

Teknisk data

Product dimensions

Reference	Dimensioner										
	Best. nr.	Andre			Dimensioner[mm]						
		DB nr.	NOBB nr.	Antal pr. kasse	D[mm]	L[mm]	dh[mm]	d1[mm]	lg[mm]	t_{fix}[mm]	Bit[mm]
VBS3.5X19	75520	-	55841796	200.0	3.5	19	6	2.7	19	0.7	Square

Product Dimensions Painted Head RAL 9005

Reference	Dimensioner									
	Best. nr.	Andre		Dimensioner[mm]						
		NOBB nr.	Antal pr. kasse	D[mm]	L[mm]	dh[mm]	d1[mm]	lg[mm]	t_{fix}[mm]	Bit[mm]
VBS3.5X19 RAL9005	75522	55841815	200.0	3.5	19	6	2.7	19	0.7	Square

Product Dimensions Painted Head RAL 9010

Reference	Dimensioner									
	Best. nr.	Andre		Dimensioner[mm]						
		NOBB nr.	Antal pr. kasse	D[mm]	L[mm]	dh[mm]	d1[mm]	lg[mm]	t_{fix}[mm]	Bit[mm]
VBS3.5X19 RAL9010	75521	55841800	200.0	3.5	19	6	2.7	19	0.7	Square

Simpson Strong-Tie A/S
Egeskovvej 33 8700 Horsens
tel: +45 8781 7400
info@strongtie.dk

Copyright by Simpson Strong-Tie®
Oplysningerne i dette dokument ejes eksklusivt af Simpson Strong-Tie® A/S.
De er kun gældende i forbindelse med produkter, som forhandles af Simpson Strong-Tie® A/S.