
Technical Sheet

TS
Wood Fibre to Steel Screw

Used indoors for fixing mouldings, OSB, chipboard and plywood. The wood fiberboard screw has nibs under its head for effective anchoring in the base material, and twin thread for fast speed. Can be used for steel substrates up to 1.0 in thickness.





Features

Material

Galvaniseret gul zinkstål

Features

- PH-skrue
- Forsænket hoved med ribber
- Skarp spids
- Dobbelt gevind
- Gul zinkbelagt

Applications

Suitable for

- Wood fibre board to steel

TS
Wood Fibre to Steel Screw

Teknisk data

Product dimensions

Reference	Dimensioner														
	Best. nr.	Andre				Dimensioner[mm]									
		DB nr.	NOBB nr.	Antal pr. kasse	Vægt[kg]	D[mm]	L[mm]	dh[mm]	d1[mm]	Ah[mm]	ht[mm]	lg[mm]	lp[mm]	h_t[mm]	Bit[mm]
TS3.9X28	75495	2055850	55840574	500.0	0.002	3.9	28	6.8	-	-	-	-	-	-	-
TS3.9X42	75496	2055851	55840585	500.0	0.003	3.9	42	6.8	-	-	-	-	-	-	-
TS3.9X57	75497	2055852	55840593	250.0	0.003	3.9	57	6.8	-	-	-	-	-	-	-

Simpson Strong-Tie A/S
Egeskovvej 33 8700 Horsens
tel: +45 8781 7400
info@strongtie.dk

Copyright by Simpson Strong-Tie®
Oplysningerne i dette dokument ejes eksklusivt af Simpson Strong-Tie® A/S.
De er kun gældende i forbindelse med produkter, som forhandles af Simpson Strong-Tie® A/S.