Technical Sheet

TTFF
Wood Fibre to Wood Screw

TTFF screws are used indoors for fixing mouldings, OSB, chipboard and plywood to wood. The wood fibre board screw has ribs under the head for effective countersinking in the base material. It has a coarse thread made for wood substrates.





Features

Advantages

- PH-skrue
- Forsænket hoved med ribber
- Skarp spids
- Grov gevind
- Gul zinkbelagt

Applications


Support

- Træfiberplader til træ

TTFF
Wood Fibre to Wood Screw

Teknisk data

Product dimensions



Reference	Dimensioner								
	Best. nr.	Andre				Dimensioner[mm]			
		DB nr.	NOBB nr.	Antal pr. kasse	Vægt[kg]	D[mm]	L[mm]	dh[mm]	Bit[mm]
TTFF4.2X55	75498	2055853	55841172	250.0	0.004	4.2	55	7	PH2

TTFF Samlede skruer

Reference	Dimensioner							
	Best. nr.	Andre			Dimensioner[mm]			
		DB nr.	NOBB nr.	Antal pr. kasse	D[mm]	L[mm]	dh[mm]	Bit[mm]
TTFF4.2X55 Collated	75727	2056074	55842216	1000.0	4.2	55	7	PH2

* Flat tape collated for standard auto-feed screwdrivers

Simpson Strong-Tie A/S
Egeskovvej 33 8700 Horsens
tel: +45 8781 7400
info@strongtie.dk

Copyright by Simpson Strong-Tie®
Oplysningerne i dette dokument ejes eksklusivt af Simpson Strong-Tie® A/S.
De er kun gældende i forbindelse med produkter, som forhandles af Simpson Strong-Tie® A/S.

2026-11-14

www.strongtie.dk